



KIARO![®] K-50

- Narrow Format Label Printer
- Print Labels 0.6" – 1.9" Wide

Compact Label Printer for Professional, Narrow-Width Labels

I believe in our (QuickLabel) printer. I've had a lot of other printers, I've never had anything like the Kiaro!. It has improved the quality of our product from a labeling standpoint, it's improved our productivity, it's improved our inventory control, just from the standpoint of what it does, it's been a top quality unit."

*-Jeff Kohr, CEO,
Boosted Vapor*

QuickLabel designed the Kiaro! 50 label printer to allow any business the opportunity to save money and time by printing its own professional product labels. Great for businesses with smaller-size labels or a less frequent need to print, the Kiaro! 50 is capable of producing the renowned speed and quality that the Kiaro! label printer pioneered.

Capable of printing over 68 labels per minute in 1200 dpi resolution, the Kiaro! 50 doesn't sacrifice speed for quality. The Kiaro! 50 gives you the opportunity to control your own label inventory and ensure the correct label gets printed every time – in the quality that you, and your customers, demand.

- Print speed up to 4.7 inches per second (23.5 ft per minute)
- Super print resolution up to 1200 dpi
- Print width 0.6" to 1.9"
- Under 10" tall and 10 lbs
- Ideal for printing small labels for food & beverage, cosmetic, e-liquid and other primary display labels

Kiaro! K-50 Specifications

Operation:

Ink Type:	Dye ink, (4) individual CMYK cartridges
Print Resolution:	1200 x 1200 dpi
Print Speed:	2 ips (50 mm/sec) – 4.7 ips (120 mm/sec)
Print Area:	Width: 0.6" (15 mm) – 1.9" (49 mm) Length: 1" (25 mm) – 15.6" (397 mm)
Media Sensors:	Gap, Reflective, Continuous; Non-adjustable/fixed sensors
Connectivity:	USB 2.0; Gigabit Ethernet, RJ-45 connection
Software	Kiaro!® 50 printer driver for Windows® 8, Windows 7 (32-bit and 64-bit), Windows Server 2012 / 2008 (included) Custom QuickLabel® software (included) or NiceLabel® software (optional)

Environmental & Physical:

Printer Operating:	59° F to 86° F (15° C to 30° C), 10% to 90% Relative Humidity (non-condensing) Printer should be installed on level surface with no more than 3° tilt in any axis. No longer than 8 weeks powered off or in standby. Cleaning may be required when powered on.
Power Requirements:	External, universal power supply 100 – 240 VAC 50/60Hz, 85W
Power Consumption:	Operating: 22W (max) Idle: 6W
Dimensions:	9.8" L x 5.3" W x 9.8" H (250 mm L x 134 mm W x 250 mm H)
Weight:	10.3 lbs. (4.7 kg) with supplies

Supplies:

Ink Cartridges:	Kiaro!® K-50 dye CMYK cartridges, 14.5 mL each, 13.2 mL usable
Ink Type:	High performance, water-based dye inks with extra wide color gamut that produce true-to-life color when combined with QuickLabel approved media.

Labels and Tags:

Width:	1.1" (28 mm) – 2.5" (63 mm)
Length:	1" (25 mm) – 30" (762 mm)
Thickness:	5.7 mil (0.145 mm) – 10 mil (0.255 mm)
Roll Size:	Up to 2.95" (75 mm) outside diameter
Types:	Matte Paper and Synthetic pressure-sensitive; Matte Paper and Synthetic Tag

Warranty:

Printer: 12 Month Manufacturer's Parts & Labor Warranty (excludes wear parts and supplies)



QuickLabel | Toll-free: 877-757-7978 | Tel: +1 401-828-4000
info@quicklabel.com | www.quicklabel.com